


SPECIFICATIONS

Minimum door thickness	1 3/4" (44.45mm)
Bolt lengths	8" (200mm), 16" (400mm), 24" (600mm), 39" (1000 mm)
Throw length	3/4" (20mm)
Finishes	Brushed finish to match stainless steel hardware, bronze powdercoat to match same finish hardware, gold anodized to match PVD brass hardware.

ROUND END




8" (200mm)
or
16" (400mm)
or
24" (600mm)
or
39" (1000mm)



ROUTER BIT FOR
FLUSHBOLTS
PRODUCT #
KTE2DBFORB

PART	PRODUCT CODE	DESCRIPTION
------	--------------	-------------



KTDBOE200NRG	8" (200mm) flushbolt, gold anodized
KTDBOE200NRX	8" (200mm) flushbolt, brushed metallic
KTDBOE200NRQ	8" (200mm) flushbolt, powdercoat bronze
KTDBOE400NRG	16" (400mm) flushbolt, gold anodized
KTDBOE400NRX	16" (400mm) flushbolt, brushed metallic
KTDBOE400NRQ	16" (400mm) flushbolt, powdercoat bronze
KTDBOE600NRG	24" (600mm) flushbolt, gold anodized
KTDBOE600NRX	24" (600mm) flushbolt, brushed metallic
KTDBOE600NRQ	24" (600mm) flushbolt, powdercoat bronze
KTDBOE1000NRG	39" (1000mm) flushbolt, gold anodized
KTDBOE1000NRX	39" (1000mm) flushbolt, brushed metallic
KTDBOE1000NRQ	39" (1000mm) flushbolt, powdercoat bronze

Machining For Flushbolts (Face Plate)

8" (200mm)	1-13/32" x 7-13/16" (36mm x 198mm)
16" (400mm)	1-13/32" x 15-11/16" (36mm x 398mm)
24" (600mm)	1-13/32" x 23-1/2" (36mm x 597mm)
39" (1000mm)	1-13/32" x 39-3/8" (36mm x 999mm)